

HRIADELE OKRUŽNÝCH PÍL

SCHAFTS OF CIRKULAR SAWING MACHINES

	160 NB	200 NB	200 NF	300 NB	300 NF	300 VHF	400 NB	400 VHB	400 NF	500 NB	500 VHB	500 NF	600 NB	600 NF
dĺžka (mm) length	265	300	360	315	360	440	315	395	360	545	660	600	580	640
šírka (mm) width	100	100	100	100	100	100	100	100	100	145	145	145	145	145
výška (mm) height	62	71	71	86	86	86	100	100	100	110	110	110	122	122
max. priemer pílového kotúča (mm) max. saw diameter	160	200	200	300	300	300	400	400	400	500	500	500	600	600
upínací priemer pílového kotúča (mm) chuck capacity of the saw waster	16/25	25	25	25/30	25/30	25/30	25/30	25/30	25/30	30	30	30	30	30
max. upínací priemer skľučovadla (mm) max. chuck diameter	-	-	-	-	-	13	-	13	-	-	16/20	-	-	-
priemer remenice (mm) pulley diameter	60	60	60	60	60	60	80	80	80	90	90	90	107	107
počet drážok remenice number of keyways of the pulley	1	1	2	2	2	2	2	2	2	2	2	2	3	3
rozmer remeňa (mm) driving belt size	10	10	10	10	10	10	13	13	13	17	17	17	17	17
dĺžka predĺžnia hriadeľa (mm) extensibility of the shaft	-	-	42	-	42	42/80	-	80	42	-	115	55	-	55
rozostup upínacích otvorov (mm) pitch diameter of the chucking holes	168/80	168/80	168/80	168/80	168/80	168/80	168/80	168/80	168/80	342/110	342/110	342/110	342/110	342/110
hmotnosť (kg) weight	3,7	4,0	4,5	4,2	4,6	5,2	5	5,6	5,4	11,5	12,9	12,1	13,2	13,9